



Intel® Solid-State Drive 750 Series Non-Volatile Memory Storage Solutions

PRODUCT BRIEF

Performance Unleashed

PCIe 3.0 X4 NVM Express™ SSD

The Intel® Solid State Drive (SSD) 750 Series is Intel's latest SSD for the high performance client and workstation storage market. Intel SSD 750 Series delivers the future of storage today with Intel's first PCIe® based consumer SSD, combining four lanes of PCIe 3.0 with state-of-the-art NMV Express™ (NVMe™) interface for truly amazing performance.



Uncompromised Performance

Don't settle for second best.

Maximize your computing experience with the Intel® Solid-State Drive 750 Series. By combining four lanes of PCIe 3.0 with state-of-the-art NVMe interface, the 750 Series delivers exceptional throughput performance and latency in a client PC SSD. The 750 Series is truly an industry leader; utilizing NVM Express™ allows the 750 Series to shed the burden of legacy AHCI commands. The Intel SSD 750 Series Add-In-Card (AIC) and 2.5-inch form factors enable performance not currently possible in form factors restricted by size or power.

NVM Express™

Industry Leading Storage Interface[†]

Introducing Intel's first client-focused NVMe SSD. NVM Express (NVMe) is a standard specification architected from the ground up for Non-Volatile Memory (NVM). NVMe significantly improves both random and sequential performance over SATA-based drives[†] by reducing latency, enabling high levels of parallelism, and streamlining the storage command set. NVMe provides a standards-based approach enabling broad ecosystem adoption for PCIe SSD interoperability.

Intel has worked closely with industry ecosystem partners to bring NVMe to the PC Client and Workstation market with a bootable, easy to use, plug-n-play solution.

The uncompromising performance of the 750 Series enables you to design and build richer content with larger data sets, textures or assets.

The 750 Series offers increased efficiency for engineering workloads: Computer Aided Drafting and Design (CADD), Computational Fluid Dynamics (CFD), Finite Element Analysis (FEA), and Simulation.


Add-in-Card and 2.5-inch SFF

Two Form Factors for Flexibility and Ease of Integration.

With both Add-in-Card and 2.5-inch form factors, the 750 Series eases migration from SATA to PCIe 3.0 without power or thermal limitations on performance. This allows the SSD to deliver the ultimate in performance in a variety of system form factors and configurations.

Add-in-Card. The Intel SSD 750 Series Add-in-Card (AIC) offers a dynamic solution for current and future systems with an accessible PCIe 3.0 slot.

U.2 2.5-inch Small Form Factor. The Intel SSD 750 Series U.2 2.5-inch provides a cabled solution where an accessible PCIe 3.0 slot is not available and the motherboard has been provisioned with an U.2 connector (formerly SFF-8643). This solution is attractive for small form factor and multi-GPU systems where space is a premium. This flexibility also provides a viable direct attach solution for small form designs with an U.2 connector (formerly SFF-8639) on board.



[†]Performance measured by Intel using IOMeter 1.1.0 with queue depth 32. Measurements are performed on 8 GB of Logical Block Address (LBA) range on a full SSD. System configuration: Intel® Core i7-5960X processor, Intel® X99 chipset, 16GB DDRR4 2133.

For additional performance information go to:

www.intel.com/content/www/us/en/solid-state-drives/solid-state-drives-750-series.html

Product Spotlight

- >4X Performance vs. SATA based SSDs[†]
- Excellent Performance per Dollar
- Industry Leading NVM Express™ Interface
- Exceptional Workload Efficiency

- Outstanding Immersive User Experience
- Faster Game Load Times
- Ultra High Definition (4K) Video Creation

Intel® Solid-State Drive 750 Series

Technical Specifications ¹		
Model Name	Intel® Solid-State Drive 750 Series	
Capacities	Half-Height Half-Length (HHHL) Add-in-Card (AIC): 400GB, 800GB, and 1.2TB 2.5-inch Small Form Factor U.2: 400GB, 800GB, and 1.2TB	
NAND Flash Memory	20nm Intel® NAND Flash Memory Multi-Level Cell (MLC)	
Sustained Sequential Reads / Writes		
Bandwidth ²	Add-in Card	2.5-inch (U.2)
	400GB: up to 2200 / 900 MB/s	400GB: up to 2200 / 900 MB/s
	800GB: up to 2100 / 800 MB/s	800GB: up to 2100 / 800 MB/s
	1.2TB: up to 2500 / 1200 MB/s	1.2TB: up to 2500 / 1200 MB/s
Read /Write Latency	20 μs / 20 μs	
4KB Reads / Writes		
Random I/O Operations per Second ²	Add-in Card	2.5-inch (U.2)
	400GB: up to 430,000 / 230,000 IOPs	400GB: up to 430,000 / 230,000 IOPs
	800GB: up to 420,000 / 210,000 IOPs	800GB: up to 420,000 / 210,000 IOPs
	1.2TB: up to 460,000 / 290,000 IOPs	1.2TB: up to 460,000 / 290,000 IOPs
Interface	PCIe 3.0 X4	
Form Factor, Height and	Add-in Card	2.5-inch (U.2)
Weight	68.9mm / 18.74mm / 168mm up to 195 grams	15mm / 70mm / 101mm / up to 125 grams
Life Expectancy ³	1.2million hours Mean Time Between Failures (MTBF)	
Lifetime Endurance ³	70GB Writes per Day	
Power Consumption Typical	400GB 800GB 1.2TB	400GB 800GB 1.2TB
	Active Read: 9W 9W 10W	Active Read: 9W 9W 10W
	Active Write: 12W 15W 22W	Active Write: 12W 15W 22W
	Idle: 4W 4W 4W	Idle: 4W 4W 4W
Operating Temperature	0° C to 70° C	
RoHS Compliance	Meets the requirements of European Union (EU) RoHS Compliance Directives	
Product Health Monitoring	Self-Monitoring, Analysis and Reporting Technology (S.M.A.R.T.) commands	
Product Ordering Information	To order, visit intel.com/ssd	
Software Tools	Intel® Solid-State Drive Toolbox at intel® Content Data Migration Software at intel® Data Migration Software at intel.com/ssdinstallation	

- 1. Based on Intel® SSD 750 Series Product Specification: http://www.intel.com/content/www/us/en/solid-state-drives/ssd-750-spec.html
- 2. Performance measured by Intel using IOMeter* 1.1.0 with queue depth 32. Measurements are performed on 8 GB of Logical Block Address (LBA) range on a full SSD.
- 3. All documented endurance test results are obtained in compliance with JESD218 Standards. See www.jedec.org for detailed definitions of JESD218 Standards.

Tests document performance of components on a particular test, in specific systems. Differences in hardware, software, or configuration will affect actual performance. Consult other sources of information to evaluate performance as you consider your purchase.

Test and System Configuration: Processor: Intel Core i7-4790K, Speed: 4.0 GHz, Chipset: Intel Z97, Motherboard: ASUS z97-Deluxe, DRAM capacity: 4GB, DRAM Speed: DDR3 2133 MHz, OS: Windows* 8.1.

All documented endurance test results are obtained in compliance with JESD218 Standards. See www.jedec.org for detailed definitions of JESD218 Standards.

The products described in this document may contain design defects or errors known as errata which may cause the product to deviate from published specifications. Current characterized errata are available on request. Contact your local Intel sales office or your distributor to obtain the latest specifications and before placing your product order. Copies of documents which have an order number and are referenced in this document, or other Intel literature, may be obtained by calling 1-800-548-4725, or by visiting Intel's Web site at www.intel.com.

*Other names and brands may be claimed as the property of others.

Copyright © 2015 Intel Corporation. All rights reserved. Intel, the Intel logo, and Intel Inside are trademarks of Intel Corporation in the U.S. and other countries.

Printed in the USA 150730, tlm 332174-002US